



BD 80 GX

TECHNICAL DATASHEET BD 80 GX



GALAXY "GX"



For illustrative purposes only

ENGINE

Description	BAUDOUIN
Engine model	4M10G88/5
Cylinders	4
RPM speed	1500
Cubic capacity	4.09 l
Air intake	Turbocharged
Standard voltage	12 Vdc
Optional voltage	Vdc
Sae	3-11
BMEP	1570 kPa
Cooling	Water
Flywheel P.R.P. Power net	70.5 kW
Flywheel Stand-by Power net	78.5 kW
Fuel Cons. at 100% (L.T.P.)	21.3 l/h
Fuel Cons. at 100% (P.R.P.)	18.8 l/h
Fuel Cons. at 75% (P.R.P.)	13.5 l/h
Fuel Cons. at 50% (P.R.P.)	9.1 l/h
Fuel Cons. at 25% (P.R.P.)	5.3 l/h
Electronic regulator	Standard
Precision class	G3
Oil quantity	13.0 l
Engine Antifreeze capacity	9.4 l
Radiator type	TR
Heat from radiator	51.4 kW
Heat from exhaust	65.1 kW
Heat from radiation	10.8 kW
Exhaust temperature	570 °C
Portata Raffreddamento	146.0 m³/min
Combustion air flow	4.8 m³/min
Exhaust gas flow	17.3 m³/min
TA Luft	N
TA Luft/2	N
EPA	N
Stage	N

MAIN DATA

Continuous power (PRP)	80.00 kVA
Continuous power (PRP)	64.00 kW
Stand-by power (LTP)	88.00 kVA
Stand-by power (LTP)	70.40 kW
VAC - HZ - cos(fi)	400 - 50 - 0.8
Sound pressure 7 m.	67 dBA

DIMENSIONS AND WEIGHT

Width	1040 mm
Length	2560 mm
Height	1805 mm
Weight	1400 kg

ALTERNATOR

Description	STAMFORD
Alternator model	UCI224G
P.R.P. Power	85 kVA
L.T.P. Power	90.8 kVA
Connection	Series star
Phases	3FN
Winding	311
Terminal Number	12 nr.
IP Protection	23
Electronic regulator	AS440
Precision	1 ± %

BASEFRAME

Model	GV060HD
Standard tank	160 l
Optional tank	70 l
Oversized tank*	800 l

CANOPY & SILENCER

Canopy model	GV060
Silencer model	MSR/a 65
Silencer outlet diameter	76 mm

Standard reference conditions temperature 25°C, altitude 100m asl, relative humidity 30%, atmospheric pressure 100 kPa (1 bar), power factor 0.8 lag, balanced load - non distortional. Fuel consumption is nominal and refers to specific weight 0.850kg/l. Sound power values refer to free field conditions: the installation site may influence the values. Dimensions, weights and other specifications contained in the technical data sheet and related attachments are nominal, subject to tolerances and refer to the model with standard equipment; any optional and additional equipment/accessories can modify weight, dimensions, performance.

P.R.P. Prime Power-Continuous power at variable load: The power that a genset can supply in continuous service at a variable load for an unlimited number of hours per year while respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer, according to ISO8528-1. The average power supplied over time and any applicable overload must be less than the percentages stated by the Manufacturer.

L.T.P. Limited-time running power-Limited power: The maximum power that a genset can supply for a limited time respecting the maintenance intervals established in the environmental conditions stated by the Manufacturer according to ISO 8528-1. The number of hours per year is stated by the Manufacturer. Overload is not permitted.

The data contained in this document is nominal and refers to the standard equipped model and is not binding. Visa S.p.A. reserves the right to revise the information without notice per our policy of continuous product development and improvement.

